

## SHIPPING DETAILS - ITW GSE PRODUCTS SHIPPED FROM DK



MODEL	TYPE	GROSS WEIGHT Kg	NET WEIGHT Kg	DIMENSIONS IN CM			PACKING METHOD
				Length	Width	Height	
ITW 1400, 28 VDC , 400, 600 A	Fixed	130	115	76	76	95	On pallet & wrapped
	Fixed / Crated	180	115	80	80	54	Wooden crate
	Mobile	240*	240	145	95	125	Wrapped
	Mobile / Crated	320*	240	200	110	154	Wooden crate
ITW 2400 30-90 kVA	Fixed	335	320	76	76	135	On pallet & wrapped
	Fixed / Crated	385	320	80	80	154	Wooden Crate
	Horizontal/PBB	355	335	120	80	118	On pallet & wrapped
	Mobile	460*	460	185	95	125	Wrapped
	Mobile / Crated	550*	460	200	110	154	Wooden Crate
	Skidmounted	375	350	120	80	105	On pallet & wrapped
ITW 2400 30-90 kVA w. ARU	Fixed	435	420	76	76	165	On pallet & wrapped
	Fixed / Crated	485	420	80	80	184	Wooden Crate
	Horizontal/PBB	460	435	160	76	118	On pallet & wrapped
	Mobile	560*	560	220	95	125	Wrapped
	Mobile / Crated	640*	560	220	110	154	Wooden Crate
	Skidmounted	485	460	160	76	105	On pallet & wrapped
ITW 2400 120-180 kVA	Fixed	670	645	140	80	140	On pallet & wrapped
	Horizontal/PBB	685	650	140	120	100	On pallet & wrapped
Power Coil 2400	Bridgemounted	765	735	163	98	145	On pallet & wrapped
	Bridgemounted / Crated	845	735	200	110	154	Wooden Crate
ACR 2400	Bridgemounted	765	735	163	98	145	On pallet & wrapped
ITW 3400 130/2	Bridgemounted	3360	3150	330	230	195	On pallet & wrapped
ITW 3400 210/3	Bridgemounted	4280	3950	500	230	195	On pallet & wrapped
ITW 3400 210/4	Bridgemounted	4750	4450	500	230	195	On pallet & wrapped
ITW 4400	Mobile	2050*	2050	265	170	170	Wrapped
7400 eGPU	Mobile	2650*	2650	297	180	170	Wrapped
7400 JetEx 28 VDC eGPU	Mobile						Wrapped

\* Weight of mobile units are indicated without cables